



# Technologies

Page 1 of 5

Loctite 561

MSDS-No. : 153640  
V001.1  
Revision: 01.03.2007  
printing date: 24.09.2007

## 1. Identification of the substance/preparation and of the company/undertaking

**Trade name:**

Loctite 561

**Intended use:**

Sealant

**Company name:**

Henkel Loctite Adhesives Ltd  
Technologies House  
Wood Lane End  
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

Fax-no.: +44 (1442) 278071

**Emergency information:**

+353-1-4599301/+353-87-2629625/+353-1-4046444

## 2. Composition / information on ingredients

**General chemical description:**

Anaerobic Sealant

**Declaration of ingredients according to 91/155/EC:**

Hazardous components CAS-No.	EINECS	content	Classification
Bisphenol A -methacrylatoethyl ether 24448-20-2	246-263-7	> 10 - < 20 %	Xi - Irritant; R36/37/38
Cumene hydroperoxide 80-15-9	201-254-7	> 0,1 - < 1 %	O - Oxidizing; R7 T - Toxic; R23 Xn - Harmful; R21/22, R48/20/22 C - Corrosive; R34 N - Dangerous for the environment; R51, R53
Cumene 98-82-8	202-704-5	> 0,1 - < 0,5 %	R10 Xn - Harmful; R65 Xi - Irritant; R37 N - Dangerous for the environment; R51, R53
Ethenediol 107-21-1	203-473-3	> 1 - < 5 %	Xn - Harmful; R22

## 3. Hazards identification

R36/37/38 Irritating to eyes, respiratory system and skin.

#### 4. First aid measures

**Inhalation:**

Move to fresh air. If symptoms persist, seek medical advice.

**Skin contact:**

Rinse with running water and soap.  
Seek medical advice.

**Eye contact:**

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

**Ingestion:**

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.  
Seek medical advice.

#### 5. Fire fighting measures

**Suitable extinguishing media:**

carbon dioxide, foam, powder

**Special protection equipment for firefighters:**

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

**Hazardous combustion products:**

Oxides of carbon, oxides of nitrogen, irritating organic vapors., Sulphur oxides

#### 6. Accidental release measures

**Personal precautions:**

Avoid skin and eye contact.

**Environmental precautions:**

Do not let product enter drains.

**Clean-up methods:**

For small spills wipe up with paper towel and place in container for disposal.

#### 7. Handling and storage

**Handling:**

Use only in well-ventilated areas.  
Avoid skin and eye contact.  
Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation

**Storage:**

Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

## 8. Exposure controls / personal protection

### Components with specific control parameters for workplace:

Valid for

Great Britain

Basis

UK EH40 WELs

Ingredient	ppm	mg/m <sup>3</sup>	Type	Category	Remarks
cumene 98-82-8	20	100	Time Weighted Average (TWA).		EU-2000/39/EC
	50	250	Short Term Exposure Limit (STEL):		EU-2000/39/EC
			Skin designation.	Can be absorbed through the skin.	EU-2000/39/EC
	25	125	Time Weighted Average (TWA).		EH40 WEL
	50	250	Short Term Exposure Limit (STEL):		EH40 WEL
			Skin designation.	Can be absorbed through the skin.	EH40 WEL
ethanediol; ethylene glycol 107-21-1	20	52	Time Weighted Average (TWA).		EU-2000/39/EC
	40	104	Short Term Exposure Limit (STEL):		EU-2000/39/EC
			Skin designation.	Can be absorbed through the skin.	EU-2000/39/EC
		10	Time Weighted Average (TWA).		EH40 WEL
	20	52	Time Weighted Average (TWA).		EH40 WEL
	40	104	Short Term Exposure Limit (STEL):		EH40 WEL
			Skin designation.	Can be absorbed through the skin.	EH40 WEL
			Skin designation.	Can be absorbed through the skin.	EH40 WEL
				Listed.	EH40 WEL
				Listed.	EH40 WEL

### Respiratory protection:

Use only in well-ventilated areas.

### Hand protection:

The use of chemical resistant gloves such as Nitrile are recommended

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced

### Eye protection:

Wear protective glasses.

### Body protection:

Wear suitable protective clothing.

### General protection and hygiene measures:

Good industrial hygiene practices should be observed

## 9. Physical and chemical properties

Appearance

waxy  
off white

Odor:

mild

Boiling point

&gt; 150 °C (&gt; 302 °F)

Flash point

Not applicable

Vapor pressure (25 °C (77 °F))	< 13 mbar
Density ( )	1,14 g/cm <sup>3</sup>
Solubility (qualitative) (Solvent: Water)	Slight
VOC content	< 5 % (As defined in the Council Directive 2004/42/EC)

## 10. Stability and reactivity

### Conditions to avoid:

Stable

### Materials to avoid:

Reaction with strong acids.  
Reacts with strong oxidants.

## 11. Toxicological information

### Oral toxicity:

May cause irritation to the digestive tract.

### Inhalative toxicity:

Irritating to respiratory system

### Skin irritation:

Irritating to the skin

### Eye irritation:

Irritating to eyes.

## 12. Ecological information

### Mobility:

Cured adhesives are immobile.

### General ecological information:

Do not empty into drains / surface water / ground water.

## 13. Disposal considerations

### Product

#### Disposal methods:

Dispose of in accordance with local and national regulations.  
Contribution of this product to waste is very insignificant in comparison to article in which it is used

#### Waste code(EWC ):

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

### Packaging

#### Disposal methods:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.  
Disposal must be made according to official regulations.

## 14. Transport information

### General information:

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

## 15. Regulations - classification and identification

### Indication of danger:

Xi - Irritant



### Risk phrases:

R36/37/38 Irritating to eyes, respiratory system and skin.

### Safety phrases:

S23 Do not breathe vapour.

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

## 16. Other information

Full text of the R-phrases indicated by codes in this safety data sheet. The labeling of the product is indicated in Section 15.

R10 Flammable.

R21/22 Harmful in contact with skin and if swallowed.

R22 Harmful if swallowed.

R23 Toxic by inhalation.

R34 Causes burns.

R36/37/38 Irritating to eyes, respiratory system and skin.

R37 Irritating to respiratory system.

R48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.

R51 Toxic to aquatic organisms.

R53 May cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R7 May cause fire.

### Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This safety data sheet was prepared in accordance with Council Directive 67/548/EEC and its subsequent amendments, and Commission Directive 1999/45/EC.