


Type CW - Clipped Washer

Mild Steel, bright zinc plated / hot dip galvanised




Product Code	Bolt Z	Dimensions			
		Y mm	X mm	T mm	Width mm
CW12	M12	6	19.5	2.5	31
CW16	M16	8	17.5	3	38
CW20	M20	10	22	4	44
CW24	M24	12	29	4	57

Packing used to adjust the tail length of the clamp to meet differing beam flange thicknesses.

Order example: CW12 BZP

Type P1 short / P2 short

Mild Steel, malleable iron, bright zinc plated / hot dip galvanised



Product Code	Bolt Z	Dimensions				
		Y mm	X mm	T _{P1} mm	T _{P2} mm	Width mm
P1S12 P2S12	M12	6	16	6	12	30
P1S16 P2S16	M16	8	21	8	16	35
P1S20 P2S20	M20	10	23	10	20	43
P1S24 P2S24	M24	12	32	12	24	54

Packing used to adjust the tail length of the clamp to meet differing beam flange thicknesses.

Order example: P1S12 BZP

For Type BR please see the following:

- Location and End Plates, page 15
- Calculation of bolt length, page 11
- • For beams with slopes of up to 8° please use the table for beams of up to 5° slope (see page 15). NB: The flange thickness refers to t₁.

Type BR is only available with tail length 'short' and 'medium'.

